

Chemical Safety Data Sheet MSDS / SDS

1,2-Diaminopropane

Revision Date:2025-03-01 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : 1,2-Diaminopropane
CBnumber : CB2426189
CAS : 78-90-0
EINECS Number : 201-155-9
Synonyms : 1,2-diaminopropane, 1,2-Propanediamine

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 010-86108875

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word

Danger

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to.....

Hazard statements

H226 Flammable liquid and vapour

H302 Harmful if swallowed

H311 Toxic in contact with skin

H312 Harmful in contact with skin

H314 Causes severe skin burns and eye damage

H317 May cause an allergic skin reaction

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H402 Harmful to aquatic life

SECTION 3: Composition/information on ingredients

Substance

Product name	: 1,2-Diaminopropane
Synonyms	: 1,2-diaminopropane, 1,2-Propanediamine
CAS	: 78-90-0
EC number	: 201-155-9
MF	: C3H10N2
MW	: 74.12

SECTION 4: First aid measures

Description of first aid measures

General advice

Consult a physician. Show this material safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Dry powder Dry sand

Unsuitable extinguishing media

Do NOT use water jet.

Special hazards arising from the substance or mixture

Carbon oxides, Nitrogen oxides (NO_x)


Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers.

NFPA 704



HEALTH 3 Short exposure could cause serious temporary or moderate residual injury (e.g. [liquid hydrogen](#), [sulfuric acid](#), [calcium hypochlorite](#), hexafluorosilicic acid)

FIRE 3 Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions. Liquids having a flash point below 22.8 °C (73 °F) and having a boiling point at or above 37.8 °C (100 °F) or having a flash point between 22.8 and 37.8 °C (73 and 100 °F). (e.g. gasoline, [acetone](#))

REACT 0 Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, [N₂](#))

SPEC.

HAZ.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. For personal protection see section 8.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in cool place.

strongly hygroscopic Handle and store under inert gas.

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

control parameter

Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,4 mm Break through time: 480 min

Material tested: Camatril? (KCL 730 / Aldrich Z677442, Size M)

Splash contact

Material: Nature latex/chloroprene Minimum layer thickness: 0,6 mm Break through time: 30 min

Material tested: Lapren? (KCL 706 / Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full- face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Appearance	colorless liquid
Odour	pungent
Odour Threshold	No data available
pH	12 (100g/l, H ₂ O, 20°C)
Melting point/freezing point	Melting point/freezing point: -36,6 °C
Initial boiling point and boiling range	119 - 120 °C - lit.
Flash point	34 °C - closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	Upper explosion limit: 11,1 %(V) Lower explosion limit: 1,9 %(V)
Vapour pressure	19 hPa at 20 °C

Vapour density	2,56 - (Air = 1.0)
Relative density	0,87 g/cm ³ at 25 °C
Water solubility	1.000 g/l at 20 °C - soluble
Partition coefficient: n-octanol/water	log Pow: -1,8
Autoignition temperature	360 °C at 1.013,25 hPa
Decomposition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidizing properties	No data available

Other safety information

Relative vapor density

2,56 - (Air = 1.0)

SECTION 10: Stability and reactivity

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

No data available

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Nitrogen oxides (NO_x)

Other decomposition products - No data available In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 1.300 mg/kg LD50 Dermal - Rabbit - male - 430 mg/kg

Skin corrosion/irritation

Skin - Rabbit

Result: Causes severe burns.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Severe eye irritation

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Ames test

S. typhimurium Result: negative

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: TX6650000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Cough, Shortness of breath, Headache, Nausea

SECTION 12: Ecological information

Toxicity**Toxicity to fish**

LC50 - Pinephales promelas (fathead minnow) - 1.010 mg/l - 96 h

Persistence and degradability

Biodegradability aerobic - Exposure time 20 d

Result: 0 % - Not biodegradable. (OECD Test Guideline 301D)

Bioaccumulative potential

No data available

Mobility in soil

No data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Other adverse effects

No data available

SECTION 13: Disposal considerations

Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

UN number

ADR/RID: 2258 IMDG: 2258 IATA: 2258

UN proper shipping name

	ADR/RID: 1,2-PROPYLENEDIAMINE IMDG: 1,2-PROPYLENEDIAMINE	
	IATA: 1,2-Propylenediamine	
14.3	Transport hazard class(es)	
	ADR/RID: 8 (3) IMDG: 8 (3)	IATA: 8 (3)
14.4	Packaging group	
	ADR/RID: II IMDG: II	IATA: II
14.5	Environmental hazards	
	ADR/RID: no IMDG Marine pollutant: no	IATA: no
14.6	Special precautions for user	
	No data available	

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015: Listed. website: <https://www.mem.gov.cn/>

Measures for Environmental Management of New Chemical Substances

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC): Listed. website: <https://www.mee.gov.cn/>

EC Inventory: Listed.

European Inventory of Existing Commercial Chemical Substances (EINECS):Listed. website: <https://echa.europa.eu/>

Korea Existing Chemicals List (KECL):Listed. website: <http://ncis.nier.go.kr>

New Zealand Inventory of Chemicals (NZIoC):Listed. website: <https://www.epa.govt.nz/>

Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: <https://emb.gov.ph/>

United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: <https://www.epa.gov/>

Vietnam National Chemical Inventory:Listed. website: <https://chemicaldata.gov.vn/>

SECTION 16: Other information

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS: Chemical Abstracts Service

EC50: Effective Concentration 50%

IATA: International Air Transportation Association

IMDG: International Maritime Dangerous Goods

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

STEL: Short term exposure limit

TWA: Time Weighted Average

References

【1】 CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>

【2】 ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

【3】 ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

【4】 eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:
http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en

【5】 ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>

【6】 Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>

【7】 HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>

【8】 IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>

【9】 IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>

【10】 Sigma-Aldrich, website: <https://www.sigmaaldrich.com/>

Other Information

Immediate administration of an appropriate inhalation therapy by a doctor, or by an authorized person, should be considered. The symptoms of lung oedema often do not become manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation are therefore essential. Other melting points: -37°C (technical product).

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.