

Chemical Safety Data Sheet MSDS / SDS

2 DIESEL FUEL

Revision Date:2026-05-31 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : 2 DIESEL FUEL
CBnumber : CB8500672
CAS : 68334-30-5
EINECS Number : 269-822-7
Synonyms : diesel,2 DIESEL FUEL

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 010-86108875

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word

Danger

Precautionary statements

P201 Obtain special instructions before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P273 Avoid release to the environment.
P308+P313 IF exposed or concerned: Get medical advice/attention.

Hazard statements

H226 Flammable liquid and vapour
H304 May be fatal if swallowed and enters airways
H315 Causes skin irritation
H332 Harmful if inhaled
H351 Suspected of causing cancer

H373 May cause damage to organs through prolonged or repeated exposure

H411 Toxic to aquatic life with long lasting effects

SECTION 3: Composition/information on ingredients


Substance

Product name : 2 DIESEL FUEL
Synonyms : diesel, 2 DIESEL FUEL
CAS : 68334-30-5
EC number : 269-822-7

SECTION 4: First aid measures

SECTION 5: Firefighting measures

NFPA 704



■ HEALTH 1 Exposure would cause irritation with only minor residual injury (e.g. [acetone](#), sodium bromate, potassium chloride)

Must be moderately heated or exposed to relatively high ambient temperature before ignition can occur and multiple finely

■ FIRE 2 divided suspended solids that do not require heating before ignition can occur. Flash point between 37.8 and 93.3 °C (100 and 200 °F). (e.g. diesel fuel, [sulfur](#))

■ REACT 0 Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, [N2](#))

□ SPEC.

□ HAZ.

SECTION 6: Accidental release measures

SECTION 7: Handling and storage

SECTION 8: Exposure controls/personal protection

control parameter**Hazard composition and occupational exposure limits**

Does not contain substances with occupational exposure limits.

SECTION 9: Physical and chemical properties

SECTION 10: Stability and reactivity

SECTION 11: Toxicological information

SECTION 12: Ecological information

SECTION 13: Disposal considerations

SECTION 14: Transport information

SECTION 15: Regulatory information

SECTION 16: Other information**Disclaimer:**

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.