

Chemical Safety Data Sheet MSDS / SDS

2-Phenylethylamine

Revision Date:2026-05-31 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : 2-Phenylethylamine
CBnumber : CB0738336
CAS : 64-04-0
EINECS Number : 200-574-4
Synonyms : phenethylamine, Phenylethylamine

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 010-86108875

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word

Danger

Precautionary statements

P234 Keep only in original container.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continuerinsing.

Hazard statements

H290 May be corrosive to metals
H301 Toxic if swallowed
H314 Causes severe skin burns and eye damage

SECTION 3: Composition/information on ingredients

Substance

Product name	: 2-Phenylethylamine
Synonyms	: phenethylamine, Phenylethylamine
CAS	: 64-04-0
EC number	: 200-574-4
MF	: C ₈ H ₁₁ N
MW	: 121.18

SECTION 4: First aid measures

General advice

First aiders need to protect themselves. Show this safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

If swallowed: give water to drink (two glasses at most). Seek medical advice immediately. In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g in a 10% slurry) and consult a doctor as quickly as possible. Do not attempt to neutralise.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

Protection of first-aiders

For personal protection see section 8.

Notes to physician

No data available

SECTION 5: Firefighting measures

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Specific hazards during fire fighting

Combustible. Vapours are heavier than air and may spread along floors. Forms explosive mixtures with air on intense heating. Development of hazardous combustion gases or vapours possible in the event of fire.

Hazardous combustion products

Carbon oxides Nitrogen oxides (NO_x)


Specific extinguishing methods

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapours/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Special protective equipment for fire-fighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

NFPA 704



■ HEALTH 3 Short exposure could cause serious temporary or moderate residual injury (e.g. [liquid hydrogen](#), [sulfuric acid](#), [calcium hypochlorite](#), hexafluorosilicic acid)

■ FIRE 2 Must be moderately heated or exposed to relatively high ambient temperature before ignition can occur and multiple finely divided suspended solids that do not require heating before ignition can occur. Flash point between 37.8 and 93.3 °C (100 and 200 °F). (e.g. diesel fuel, [sulfur](#))

■ REACT 1 Normally stable, but can become unstable at elevated temperatures and pressures (e.g. [propene](#))

□ SPEC.
□ HAZ.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: For personal protection see section 8.

Environmental precautions

Do not let product enter drains.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material. Dispose of properly. Clean up affected area.

SECTION 7: Handling and storage

Handling

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Storage

Conditions for safe storage

No metal containers.

Further information on storage conditions

Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorised persons.

Storage class

6.1A, Combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials

Recommended storage temperature

Recommended storage temperature see product label.

Further information on storage stability

Store under inert gas. Air sensitive.

SECTION 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures

No data available

Personal protective equipment

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter

Filter A (acc. to DIN 3181) for vapours of organic

type

compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Tightly fitting safety goggles

Skin and body protection

protective clothing

Hand protection**Material**

butyl-rubber

Break through time

480 min

Glove thickness

0.7 mm

Protective index

Full contact

Manufacturer

Butoject® (KCL 898)

Material

Nitrile rubber

Break through time

10 min

Glove thickness

0.4 mm

Protective index

Splash contact

Manufacturer

Camatril® (KCL 730 / Aldrich Z677442, Size M)

Remarks

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D- 36124 Eichenzell, Internet: www.kcl.de).

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

liquid (20 °C , 1,013 hPa)

Color

colourless

Odor

amine-like

Odor Threshold

No data available

pH

11.5 (20 °C)

Concentration: 4.3 g/l

Melting point/ range

< -60 °C

Boiling point/boiling range

197 - 200 °C

Method: lit.

Flash point

81 °C

Method: Tested according to Annex V of Directive 67/548/EEC., closed cup

Evaporation rate

No data available

Burning rate

No data available

Self-ignition

425 °C

Upper explosion limit / Upper flammability limit

5.5 %(V)

Lower explosion limit / Lower flammability limit

1.0 %(V)

Vapor pressure

0.4 hPa (20 °C) 5.1 hPa (50 °C)

Relative vapor density

4.19

Relative density

0.96 (24.8 °C)

Density

0.962 g/mL (20 °C)

Method: lit.

Water solubility

63.25 g/l (25 °C)

Partition coefficient: n-octanol/water

log Pow: 1.41

Method: (calculated) (Lit.) Bioaccumulation is not expected.

Autoignition temperature

425 °C

Method: DIN 51794

Decomposition temperature

To avoid thermal decomposition, do not overheat.

Viscosity, dynamic

3.07 mPa.s (25 °C)

Viscosity, kinematic

2.40 mm²/s (23 °C)

Flow time

No data available

Explosive properties

No data available

Oxidizing properties

none

Molecular weight

121.18 g/mol

Particle characteristics Particle size

No data available

Metal corrosion rate

May be corrosive to metals.

Solubility

alcohol: freely soluble(lit.)

Physical state

liquid

Viscosity

2.40 mm²/s at 23 °C

SECTION 10: Stability and reactivity

Reactivity

Forms explosive mixtures with air on intense heating. A range from approx. 15 Kelvin below the flash point is to be rated as critical.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

Caution! In contact with nitrites, nitrates, nitrous acid possible liberation of nitrosamines! Exothermic reaction with: Acid chlorides Acid anhydrides Strong oxidizing agents acids

Conditions to avoid

Air Strong heating.

Incompatible materials

No data available

Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 287 mg/kg

Remarks: (ECHA)

Inhalation: No data available

Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Causes burns.

Remarks: (ECHA)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye damage. - 1 h

Remarks: (ECHA)

Respiratory or skin sensitization

Classified based on available data. For more details, see section 2

Germ cell mutagenicity

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Carcinogenicity

Classified based on available data. For more details, see section 2

Reproductive toxicity

Classified based on available data. For more details, see section 2

Specific target organ toxicity - single exposure

Classified based on available data. For more details, see section 2

Specific target organ toxicity - repeated exposure

Classified based on available data. For more details, see section 2

Aspiration hazard

Classified based on available data. For more details, see section 2

11.2 Additional Information

RTECS: SG8750000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Cough, Shortness of breath, Headache, Nausea,

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

Ecotoxicity**Components:****2-phenylethylamine:****Toxicity to fish**

LC50 (Leuciscus idus (Golden orfe)): 38.3 mg/l End point: mortality Exposure time: 96 h Test Type: static test Method: DIN 38412 part 15

Toxicity to microorganisms

EC50 (Pseudomonas putida): 270 mg/l Exposure time: 17 h Test Type: static test Method: DIN 38421 TEIL 8

Ecotoxicology Assessment**Chronic aquatic toxicity**

This product has no known ecotoxicological effects.

Persistence and degradability**Components:****2-phenylethylamine:**

Biodegradability

aerobic Concentration: 100 mg/l Result: Readily biodegradable. Biodegradation: 95 % Exposure time: 14 Days Method: OECD Test Guideline 301C

BOD/COD

BOD/COD: > 60 % Remarks: (External MSDS)

Bioaccumulative potential**Components:****2-phenylethylamine:****Bioaccumulation**

Remarks: Does not bioaccumulate.

Partition coefficient: noctanol/water

log Pow: 1.41 Method: (calculated) Remarks: (Lit.) Bioaccumulation is not expected.

Mobility in soil

No data available

Other adverse effects**Components:****2-phenylethylamine:****Additional ecological information**

Do not empty into drains.

SECTION 13: Disposal considerations

Disposal methods**Waste from residues**

Offer surplus and non-recyclable solutions to a licensed disposal company.

SECTION 14: Transport information

International Regulations**IATA-DGR**

UN/ID No. : UN 2922

Proper shipping name : Corrosive liquid, toxic, n.o.s.

(2-phenylethylamine)

Class : 8

Subsidiary risk : 6.1

Packing group : II

Labels : Class 8 - Corrosive substances, Division 6.1 - Toxic substances

Packing instruction (cargo aircraft) : 855

Packing instruction (passenger aircraft) : 851

IMDG-Code

UN number : UN 2922

Proper shipping name : CORROSIVE LIQUID, TOXIC, N.O.S.

(2-phenylethylamine)

Class : 8

Subsidiary risk : 6.1

Packing group : II

Labels : 8 (6.1)

EmS Code : F-A, S-B

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

JT/T 617

UN number : UN 2922

Proper shipping name : CORROSIVE LIQUID, TOXIC, N.O.S.

(2-phenylethylamine)

Class : 8

Subsidiary risk : 6.1

Packing group : II

Labels : 8 (6.1)

Environmentally hazardous : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information

National regulatory information

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals

Hazardous Chemicals for Priority Management

Not applicable under SAWS

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import and Export

Not applicable

SECTION 16: Other information

Full text of other abbreviations

AIRC - Australian Inventory of Industrial Chemicals

ANTT - National Agency for Transport by Land of Brazil

ASTM - American Society for the Testing of Materials

bw - Body weight

CMR - Carcinogen, Mutagen or Reproductive Toxicant

DIN - Standard of the German Institute for Standardisation

DSL - Domestic Substances List (Canada)

EC_x - Concentration associated with x% response

EL_x - Loading rate associated with x% response

EmS - Emergency Schedule

ENCS - Existing and New Chemical Substances (Japan)

ErC_x - Concentration associated with x% growth rate response

ERG - Emergency Response Guide

GHS - Globally Harmonised System

GLP - Good Laboratory Practice

IARC - International Agency for Research on Cancer

IATA - International Air Transport Association

IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

IC₅₀ - Half maximal inhibitory concentration

ICAO - International Civil Aviation Organization

IECSC - Inventory of Existing Chemical Substances in China

IMDG - International Maritime Dangerous Goods

IMO - International Maritime Organisation

ISHL - Industrial Safety and Health Law (Japan)

ISO - International Organisation for Standardisation

KECI - Korea Existing Chemicals Inventory

LC₅₀ - Lethal Concentration to 50 % of a test population

LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)

MARPOL - International Convention for the Prevention of Pollution from Ships

MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods

n.o.s. - Not Otherwise Specified

Nch - Chilean Norm

NO(A)EC - No Observed (Adverse) Effect Concentration

NO(A)EL - No Observed (Adverse) Effect Level

NOELR - No Observable Effect Loading Rate

NOM - Official Mexican Norm

NTP - National Toxicology Program

NZIoC - New Zealand Inventory of Chemicals

OECD - Organisation for Economic Co-operation and Development

OPPTS - Office of Chemical Safety and Pollution Prevention

PBT - Persistent, Bioaccumulative and Toxic substance

PICCS - Philippines Inventory of Chemicals and Chemical Substances

(Q)SAR - (Quantitative) Structure Activity Relationship

REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals

SADT - Self-Accelerating Decomposition Temperature

SDS - Safety Data Sheet

TCSI - Taiwan Chemical Substance Inventory

TDG - Transportation of Dangerous Goods

TECI - Thailand Existing Chemicals Inventory

TSCA - Toxic Substances Control Act (United States)

UN - United Nations

UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods

vPvB - Very Persistent and Very Bioaccumulative

WHMIS - Workplace Hazardous Materials Information System

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.