

Chemical Safety Data Sheet MSDS / SDS

TETRAETHYLLEAD

Revision Date:2026-05-31 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product identifier**

Product name : TETRAETHYLLEAD
CBnumber : CB0784388
CAS : 78-00-2
EINECS Number : 201-075-4
Synonyms : tetraethyllead,tel

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 010-86108875

SECTION 2: Hazards identification**GHS Label elements, including precautionary statements**

Symbol(GHS)



Signal word

Danger

Precautionary statements

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P201 Obtain special instructions before use.

Hazard statements

H410 Very toxic to aquatic life with long lasting effects
H373 May cause damage to organs through prolonged or repeated exposure

SECTION 3: Composition/information on ingredients


Substance

Product name	: TETRAETHYLLEAD
Synonyms	: tetraethyllead,tel
CAS	: 78-00-2
EC number	: 201-075-4
MF	: C8H20Pb
MW	: 323.44

SECTION 4: First aid measures

SECTION 5: Firefighting measures

NFPA 704



<input checked="" type="checkbox"/> HEALTH	3	Short exposure could cause serious temporary or moderate residual injury (e.g. liquid hydrogen , sulfuric acid , calcium hypochlorite , hexafluorosilicic acid)
<input checked="" type="checkbox"/> FIRE	2	Must be moderately heated or exposed to relatively high ambient temperature before ignition can occur and multiple finely divided suspended solids that do not require heating before ignition can occur. Flash point between 37.8 and 93.3 °C (100 and 200 °F). (e.g. diesel fuel, sulfur)
<input checked="" type="checkbox"/> REACT	2	Undergoes violent chemical change at elevated temperatures and pressures, reacts violently with water, or may form explosive mixtures with water (e.g. white phosphorus, potassium , sodium)
<input type="checkbox"/> SPEC.		
<input type="checkbox"/> HAZ.		

SECTION 6: Accidental release measures

SECTION 7: Handling and storage

SECTION 8: Exposure controls/personal protection

control parameter**Hazard composition and occupational exposure limits**

Does not contain substances with occupational exposure limits.

SECTION 9: Physical and chemical properties

SECTION 10: Stability and reactivity

SECTION 11: Toxicological information

SECTION 12: Ecological information

SECTION 13: Disposal considerations

SECTION 14: Transport information

SECTION 15: Regulatory information

SECTION 16: Other information**Disclaimer:**

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.