

Chemical Safety Data Sheet MSDS / SDS

Bromoethane

Revision Date:2026-03-21 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : Bromoethane
CBnumber : CB8408624
CAS : 74-96-4
EINECS Number : 200-825-8
Synonyms : ETHYL BROMIDE

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 010-86108875

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word

Danger

Precautionary statements

P502 Refer to manufacturer/supplier for information on recovery/recycling
P308+P313 IF exposed or concerned: Get medical advice/attention.
P301+P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P202 Do not handle until all safety precautions have been read and understood.

Hazard statements

H420 Harms public health and the environment by destroying ozone in the upper atmosphere
H351 Suspected of causing cancer
H225 Highly Flammable liquid and vapour

SECTION 3: Composition/information on ingredients

Substance

Product name	: Bromoethane
Synonyms	: ETHYL BROMIDE
CAS	: 74-96-4
EC number	: 200-825-8
MF	: C ₂ H ₅ Br
MW	: 108.97

SECTION 4: First aid measures

General advice

Show this safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

Protection of first-aiders

For personal protection see section 8.

Notes to physician

No data available

SECTION 5: Firefighting measures

Suitable extinguishing media

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Specific hazards during fire fighting

Combustible. Pay attention to flashback. Vapours are heavier than air and may spread along floors. Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.

Hazardous combustion products

Carbon oxides Hydrogen bromide gas


Specific extinguishing methods

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapours/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Special protective equipment for fire-fighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

NFPA 704



<input checked="" type="checkbox"/>	HEALTH	3	Short exposure could cause serious temporary or moderate residual injury (e.g. liquid hydrogen , sulfuric acid , calcium hypochlorite , hexafluorosilicic acid)
<input checked="" type="checkbox"/>	FIRE	3	Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions . Liquids having a flash point below 22.8 °C (73 °F) and having a boiling point at or above 37.8 °C (100 °F) or having a flash point between 22.8 and 37.8 °C (73 and 100 °F). (e.g. gasoline, acetone)
<input checked="" type="checkbox"/>	REACT	0	Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, N₂)
<input type="checkbox"/>	SPEC.		
<input type="checkbox"/>	HAZ.		

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: For personal protection see section 8.

Environmental precautions

Do not let product enter drains. Risk of explosion.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material. Dispose of properly. Clean up affected area.

SECTION 7: Handling and storage

Handling

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Storage

Further information on storage conditions

Keep container tightly closed in a dry and wellventilated place. Keep away from heat and sources of ignition.

Storage class

3, Flammable liquids

Recommended storage temperature

Recommended storage temperature see product label.

Further information on storage stability

Light sensitive. Refrigerate before opening. Over time, pressure may increase causing containers to burst Handle and open container with care.

Packaging material

Suitable material: Mild Steel Drum

SECTION 8: Exposure controls/personal protection

control parameter

Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

Engineering measures

No data available

Personal protective equipment

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type

Filter type AX

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the

instructions of the producer. These measures have to be properly documented.

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Safety glasses

Skin and body protection

Flame retardant antistatic protective clothing.

Hand protection

Material

Viton®

Break through time

60 min

Glove thickness

0.7 mm

Protective index

Splash contact

Manufacturer

Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Remarks

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D- 36124 Eichenzell, Internet: www.kcl.de).

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

liquid

Color

colourless

Odor

No data available

Odor Threshold

No data available

pH

No data available

Melting point/ range

-119 °C

Method: lit.

Boiling point/boiling range

37 - 40 °C

Method: lit.

Flash point

-23 °C

Method: closed cup

Evaporation rate

No data available

Flammability (solid, gas)

No data available

Flammability (liquids)

No data available

Burning rate

No data available

Upper explosion limit / Upper flammability limit

11.25 %(V)

Lower explosion limit / Lower flammability limit

6.75 %(V)

Vapor pressure

519.7 hPa (20 °C) 1,745.2 hPa (55 °C)

Relative vapor density

3.76

Relative density

1.46 g/mL at 25 °C(lit.)

Density

1.46 g/mL (25 °C)

Method: lit.

Water solubility

0.91 g/100 mL (20 °C)

Partition coefficient: n-octanol/water

No data available

Autoignition temperature

511 °C

Decomposition temperature

No data available

Viscosity, dynamic

No data available

Viscosity, kinematic

No data available

Flow time

No data available

Explosive properties

No data available

Oxidizing properties

none

Molecular weight

108.97 g/mol

Particle characteristics Particle size

No data available

Solubility

Miscible with ethanol, ether, chloroform and organic solvents.

Physical state

Liquid

Henry's Law Constant

7.56×10^{-3} atmm³/mol) at 25 °C (Hine and Mookerjee, 1975)

Dielectric constant

9.4 (20°C)

SECTION 10: Stability and reactivity

Reactivity

Vapours may form explosive mixture with air.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

Violent reactions possible with: Alkali metals Alkaline earth metals sodium amide Oxidizing agents Metals Bases

Conditions to avoid

Warming.

Incompatible materials

No data available

Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 1,350 mg/kg

Remarks: (RTECS)

Acute toxicity estimate Inhalation - 4 h - 11.1 mg/l - vapour (Expert judgement)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Dermal: No data available

Skin corrosion/irritation

Classified based on available data. For more details, see section 2

Serious eye damage/eye irritation

Classified based on available data. For more details, see section 2

Respiratory or skin sensitization

Classified based on available data. For more details, see section 2

Germ cell mutagenicity

Classified based on available data. For more details, see section 2

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Classified based on available data. For more details, see section 2

Specific target organ toxicity - single exposure

Classified based on available data. For more details, see section 2

Specific target organ toxicity - repeated exposure

Classified based on available data. For more details, see section 2

Aspiration hazard

Classified based on available data. For more details, see section 2

11.2 Additional Information

RTECS: KH6475000 narcosis, Dizziness, Weakness, Ataxia., Tremors

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

Ecotoxicity

Components:

Ethyl bromide:

Toxicity to algae/aquatic plants

ErC50 (Pseudokirchneriella subcapitata): 200 mg/l Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 GLP: yes

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13: Disposal considerations

Disposal methods

Waste from residues

Offer surplus and non-recyclable solutions to a licensed disposal company.

SECTION 14: Transport information

International Regulations

IATA-DGR

UNID No. : UN 1891

Proper shipping name : Ethyl bromide

Class : 3

Subsidiary risk : 6.1

Packing group : II

Labels : Class 3 - Flammable liquids, Division 6.1 - Toxic substances

Packing instruction (cargo aircraft) : 364

Packing instruction (passenger aircraft) : 352

IMDG-Code

UN number : UN 1891

Proper shipping name : ETHYL BROMIDE

Class : 3

Subsidiary risk : 6.1

Packing group : II

Labels : 3 (6.1)

EmS Code : F-E, S-D

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

JT/T 617

UN number : UN 1891

Proper shipping name : ETHYL BROMIDE

Class : 3

Subsidiary risk : 6.1

Packing group : II

Labels : 3 (6.1)

Environmentally hazardous : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

No. / Code Chemical name / Category Threshold quantity

W5.3 Flammable liquids 1,000 t

Hazardous Chemicals for Priority Management

Not applicable under SAWS

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import and Export

Not applicable

SECTION 16: Other information

Full text of other abbreviations

ACGIH

USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA AIC - Australian Invent Transport by Land of Bra bw - Body weight; CMR Standard of the German List (Canada); ECx - Conc associated with x%respo Chemical Substances (Jap response; ERG - Emerge GLP - Good Laboratory P cer; IATA - International Construction and Equipm Half maximal inhibitory c tion; IECSC - Inventory o tional Maritime Dangerou Industrial Safety and H Standardisation; KECl - K tration to 50 %of a test (Median Lethal Dose); MA lution from Ships; MERC of Dangerous Goods; n.o. - No Observed (Adverse) fect Level; NOELR - No Norm; NTP - National Toxi icals; OECD - Organisatio fice of Chemical Safety a and Toxic substance; PIC stances; (Q)SAR - (Quant (EC) No 1907/2006 of th Registration, Evaluation, Accelerating Decompositi Chemical Substance Inve Thailand Existing Chemica States); UN - United Nat Transport of Dangerous WHMIS - Workplace Hazar

8-hour, time-weighted average ry of Industrial Chemicals

ANTT - National Agency for il

ASTM - American Society for the Testing of Materials

- Carcinogen, Mutagen or Reproductive Toxicant

DIN nstitute for Standardisation

DSL - Domestic Substances ntration associated with x% response

ELx - Loading rate se

EmS - Emergency Schedule

ENCS - Existing and New n)

ErCx - Concentration associated with x% growth rate cy Response Guide

GHS - Globally Harmonised System

actice

IARC - International Agency for Research on Canir Transport Association

IBC - International Code for the nt of Ships carrying Dangerous Chemicals in Bulk
IC50 ncentration

ICAO - International Civil Aviation Organiza- Existing Chemical Substances in China

IMDG - Interna- Goods

IMO - International Maritime Organisation

ISHL alth Law (Japan)

ISO - International Organisation for rea Existing Chemicals Inventory

LC50 - Lethal Concentration

LD50 - Lethal Dose to 50% of a test population
POL - International Convention for the Prevention of Pollution from Ships
SUR - The Agreement for the Facilitation of the Transport of Dangerous Goods - Not Otherwise Specified

NCh - Chilean Norm

NO(A)EC - No Observed Effect Concentration

NO(A)EL - No Observed (Adverse) Effect Loading Rate

NOM - Official Mexican Nomenclature Program

NZIC - New Zealand Inventory of Chemicals for Economic Co-operation and Development

OPPTS - Office of Pollution Prevention

PBT - Persistent, Bioaccumulative and Toxic - Philippines Inventory of Chemicals and Chemical Substances Structure Activity Relationship

REACH - Regulation European Parliament and of the Council concerning the Restriction and Authorization of Chemicals

SADT - Self-Heating Temperature

SDS - Safety Data Sheet

TCSI - Taiwan Chemical Safety Inventory

TDG - Transportation of Dangerous Goods

TECS Inventory

TSCA - Toxic Substances Control Act (United States)

UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods

vPvB - Very Persistent and Very Bioaccumulative

HMIS - Hazardous Materials Information System

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.